

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification:	A1	(11) International Publication Number: WO 79/01040
C08G 63/18		(43) International Publication Date: 29 November 1979 (29.11.79)

(21) International Application Number: PCT/US79/00214

(22) International Filing Date: 5 April 1979 (05.04.79)

(31) Priority Application Number: 903,437

(32) Priority Date: 8 May 1978 (08.05.78)

(33) Priority Country: US

(71) Applicant: EASTMAN KODAK COMPANY [US/US]; 343 State Street, Rochester, NY 14650 (US).

(72) Inventors: JACKSON, Jr., Winston, Jerome; 4408 Greensprings Circle, Kingsport, TN 37664 (US). MORRIS, John Craft; 359 Summerville Road, Kingsport, TN 37663 (US). (74) Agent: KLINE, William, H., J.; Eastman Kodak Company, 343 State Street, Rochester, NY 14650 (US).

(81) Designated States: DE (European patent), FR (European patent), GB (European patent), JP.

Published with:

International search report

(54) Title: LIQUID CRYSTAL COPOLYESTERS

(57) Abstract

Liquid crystal copolyesters having melting points low enough to allow the copolyesters to be melt-processed in conventional equipment. The copolyesters are prepared from terephthalic acid, 2,6-naphthalenedicarboxylic acid, a diacyl ester of hydroquinone and a diacyl ester of resorcinol and contain the following divalent radicals:

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT

AT	Austria	LU	Luxembourg
BR	Brazil	MC .	Monaco
CF	Central African Empire	MG	Madagascar
CG	Congo	MW	Malaŵi
CH	Switzerland	NL	Netherlands
CM	Cameroon	RO	Romania
DE	Germany, Federal Republic of	SE	Sweden
DK	Denmark	SN	Senegal
FR		SU	Soviet Union
GA	Gabon	TD	Chad
GB	United Kingdom	TG	Togo
JP	Japan	US	United States of America
4 L	- of-	`•	•

LIQUID CRYSTAL COPOLYESTERS

Technical Field

This invention relates to liquid crystal co-5 polyesters having the high mechanical properties of liquid crystal copolyesters and melting points low enough to allow the copolyesters to be melt-processed into useful articles using commercially available equipment.

10 Background of the Invention

Liquid crystal copolyesters that are all-aromatic have excellent mechanical properties. Examples of these polyesters are the copolyesters prepared from terephthalic acid, 2,6-naphthalenedicarboxylic acid, 15 hydroquinone and resorcinol. U.S. Patents 3,160,602 and 3,778,410 describe processes that can be used to prepare these copolyesters. It has been difficult to use these copolyesters because the melting points of the polymers have been so high that the polymers cannot be melted 20 and formed into useful articles in conventional processing equipment.

Disclosure of Invention

We have found that certain all-aromatic copolyesters prepared from terephthalic acid, 2,6-25 naphthalene dicarboxylic acid, hydroquinone and resorcinol have melting points that are low enough to permit the copolyesters to be processed into useful articles, such as fibers and molded articles, in conventional equipment.

The copolyesters of this invention are prepared 30 from terephthalic acid, 2,6-naphthalenedicarboxylic acid, a diacyl ester of hydroquinone and a diacyl ester of resorcinol and can be defined as copolyesters having molecular weights suitable for forming fibers and containing the following divalent radicals:

15

5

In our copolyesters the range of terephthalic acid is from 20 to 50 mole percent, based on the total moles of terephthalic acid and 2,6-naphthalenedicarboxylic acid combined. Since the range of terephthalic acid is based on the sum of the moles of terephthalic acid and 2,6-naphthalenedicarboxylic acid, at 20 mole percent terephthalic acid the copolyesters have 80 mole percent 2,6-naphthalenedicarboxylic acid and at 50 mole percent terephthalic acid the copolyesters have 50 mole percent 2,6-naphthalenedicarboxylic acid.

In preferred copolyesters the range of terephthalic acid is from 30 to 45 mole percent, based on the total moles of terephthalic acid and 2,6-naphthalenedicarboxylic acid combined.

Also in our copolyesters the amount of resorcinol is from 20 to 65 mole perent, based on the total moles of hydroquinone and resorcinol combined. Thus, at 25 mole percent resorcinol, the copolyesters have 75 mole percent hydroquinone, and at 65 mole percent resorcinol the copolyesters have 35 mole percent hydroquinone.

In preferred copolyesters the range of resorcinol is from 30 to 50 mole percent, based on the total moles of resorcinol and hydroquinone.

10

20

The precise manner in which the melting points of the copolyesters of the invention are unexpectedly lower than the melting points of similar copolyesters is illustrated in the Figure.

In the Figure the amount of terephthalic acid, based on the total moles of terephthalic acid and 2,6naphthalenedicarboxylic acid, has been plotted on the abscissa. The temperature in degrees Centigrade has been plotted on the ordinate. Melting points have been plotted for copolyesters of the invention, containing a quantity of terephthalic acid in the range of 20 to 50 mole percent, based on the total moles of terephthalic acid and 2,6-naphthalenedicarboxylic acid. Suitable curves have been drawn through the data points 15 for copolyesters containing the same amount of resor-For example, the lowermost curve drawn through the closed circular data points represents the melting points of copolyesters containing 40 mole percent resorcinol, based on the total moles of hydroquinone and resorcinol combined.

> The data for the copolyesters of the invention were obtained by preparing each of the copolyesters using a process known in the art and then determining the melting points of each copolyester.

The copolyesters of the invention were pre-.25 pared by an acidolysis procedure whereby terephthalic acid, 2,6-naphthalenedicarboxylic acid, a diacyl ester of hydroquinone and a diacyl ester of resorcinol were reacted under an increasing temperature ranging up to $340-380^{\circ}\mathrm{C}$. and a decreasing pressure to form a high 30 molecular weight polymer. As a specific example, the following procedure was used to prepare a copolyester from 40 mole percent terephthalic acid and 60 mole percent 2,6-naphthalenedicarboxylic acid, based on the moles of terephthalic acid and 2,6-naphthalenedicarboxy-35 lic acid combined, and 60 mole percent hydroquinone and

20

25

30

40 mole percent resorcinol, based on the moles of hydroquinone and resorcinol combined.

A mixture of 33.2 g. (0.20 mole) terephthalic acid, 64.8 g. (0.30 mole) 2,6-naphthalenedicarboxylic acid, 38.8 g. (0.20 mole) resorcinol diacetate, and 66.6 g. (0.30 mole) hydroquinone dipropionate was placed in a 500-ml. flask equipped with a stirrer, short distillation column and an inlet for nitrogen. The flask was evacuated and purged three times with nitrogen and dried at 100-110°C. for 30 minutes at <0.3 mm. pressure before being immersed in a bath at 275°C. After the mixture was stirred for 30 minutes at 280°C., the temperature was raised to 300°C. for 30 minutes and then to 325°C. for 30 minutes. Finally the temperature was raised to 355°C. for 25 minutes and a vacuum of 0.5 mm. was ap-The polymerization was complete within 20 to 30 minutes. The tough, fibrous, opaque polymer obtained had a softening point of 332°C. and a melting point of 341°C. Fibers with tenacities >3 g./denier can be melt spun at 360°C. Heat-treated fibers had tenacities of 10 g./denier and higher.

The other copolyesters containing different amounts of 2,6-naphthalenedicarboxylic acid, terephthalic acid, hydroquinone and resorcinol were prepared by a similar procedure but using slightly different reaction temperatures because of differences in melting points.

Solid-phase polymerization also may be used to increase the molecular weight of the copolyesters of the invention by heating polymer particles in an inert atmosphere or under reduced pressure at a temperature below that at which the particles will become tacky and tend to fuse together. Since this thermal treatment may give polymers with increased crystall-inity and melting points, compared to melt phase

1333

10

15

20

polymerization, melt phase polymerization is generally preferred. Solid-phase polymerization is preferred, however, if the melting point is above 380°C.

The melting points of the copolyesters of the invention were determined with a differential scanning calorimeter.

The accompanying Figure shows that the melting points of the copolyesters of the invention containing 20 to 50 mole percent terephthalic acid and 20 to 65 mole percent resorcinol are unexpectedly lower than the melting points of copolyesters containing less than 20 or more than 50 mole percent terephthalic acid. For example, consider the copolyester which contains a constant value of 40 mole percent resorcinol and is represented by the lower curve connecting the closed circular data points. When the amount of terephthalic acid is below 20 mole percent, the melting point is above 400°C. As the amount of terephthalic acid is increased, the melting point falls and reaches a minimum value of 330°C. at 30 mole percent terephthalic acid. amount of terephthalic acid is increased, the melting point increases and is 385°C. at 50 mole percent terephthalic acid.

25 melting point have been discussed only for the copolyesters containing 40 mole percent resorcinol, the same
lowering of the melting point applies to the other copolyesters of this invention. For example, the melting
point of the copolyesters containing 20 and 60 mole per30 cent resorcinol is also substantially lowered when from
20 to 50 mole percent terephthalic acid is used. Although melting point data is not plotted for copolyesters containing less than 20 mole percent terephthalic
acid, it is clear from the shape of the curve melting
35 points are above 400°C.

10

15

A wide variety of diacyl esters of hydroquinone and resorcinol can be used to prepare the copolyesters of this invention. Examples of diesters include
the diacetate, dipropionate, dibutyrate and dibenzoate.
The diacetate and dipropionate are preferred.

The copolyesters of this invention can contain minor amounts of other naphthalenedicarboxylic acid isomers in addition to the 2,6-isomer. Also, minor amounts of dicarboxylic acids other than terephthalic acid and diols other than hydroquinone can be used. The copolyesters of this invention can also contain nucleating agents, fillers, pigments, glass fibers, asbestos fibers, antioxidants, stabilizers, plasticizers, lubricants, fire-retardants, and other additives.

The inherent viscosity of the copolyesters of this invention cannot be determined because the copolyesters of this invention are insoluble in typical solvents used for determining inherent viscosity. Although the inherent viscosity of the copolyesters of the invention has not been measured, the molecular weights of the copolyesters of the invention are high enough to be in the fiber-forming range. The minimum fiber-forming molecular weight of the copolyesters is about 5,000. In most cases copolyesters of the invention have molecular weights above 8,000 and can have molecular weights as high as 20,000 and in some instances the molecular weights can range up to 25,000 or even higher.

25

We Claim:

Copolyesters having a fiber-forming molecular weight and containing the following divalent radicals:


15

the copolyesters being characterized by the amount of

being from 20 to 50 mole percent,

20

based on the total moles of




combined, and the amount of

25

-O- being from 20 to 65 mole percent,

based on the total moles of -0-



30

1773

The copolyester of Claim 1 wherein the 2.



45 mole percent and the range of the amount of 35 .

-0-

is from 30 to 50 mole percent.

5

1 01 00			International Application No PCT	C/US79/00214	
1. CLAS	SIFICATIO	N OF SUBJECT MATTER (if several d	assification symbols apply, indicate all) *		
		ional Patent Classification (IPC) or to both	National Classification and IPC		
	L. C08				
0.5.	CL. 52	28/190	·		
II. FIELD	S SEARCH	ED			
		Minimum Docu	mentation Searched 4		
Classificat	ion System		Classification Symbols		
			Coassincation Sympols	· 	
US		528/190; 528/193	; 528/194	٠.	
	<u>-</u>	Documentation Searched oth to the Extent that such Docume	er than Minimum Documentation nts are included in the Fields Searched 6	•	
	(e e).			*	
III. DOCU	JMENTS C	DISIDERED TO BE RELEVANT 14		<u> </u>	
ategory *	~ ~~~	n of Document, 16 with indication, where a	orrondate of the minutes	10.	
				Relevant to Claim No. 18	
X	US, A	, 3,160,602, PUBLISH KANTOR	ED 08 DECEMBER 1964 R ET AL.	1-2	
X		3,778,410, PUBLISHE KUHFUS	D 11 DECEMBER 1973 S ET AL.	1-2	
A	US, A	, 4,066,620, PUBLISH KLEINSC	ED 03 JANUARY 1978 HUSTER ET AL.	1-2	
X,P	US, A	, 4,118,372, PUBLISH SCHAEF		1-2	
,		4,156,070, PUBLISHE JACKSON	D 22 MAY 1979 , JR, ET AL.	1-2	
X,E	US,A,	4153,779, PUBLISHED JACKSON,	1-2		
* * * * * * * * * * * * * * * * * * * *					
A" docum	ent defining (ited documents: 16 he general state of the art nt published on or after the international	"P" document published prior to the in	ternational filing date but	
ning as docume to in th	ate ont cited for ne other cate	special reason other than those referred gories	"T" later document published on or affidate or priority date and not in country but cited to understand the principle.	d .	
docume other m	ent referring leans	to an oral disclosure, use, exhibition or	the Invention		
. CERTIF	TCATION		A how second 3 gald duch	·	
		letion of the International Search 2	Date of Mailing of this later attends	and Day and D	
	UST 19		Date of Mailing of this International Search Report 3 1 3 AUG 1979		
ternational	Searching A	authority 1			
ISA/US Signature of Authorized Officer 10 LESTER L. LEE					

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

| BLACK BORDERS
| IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
| FADED TEXT OR DRAWING
| BLURRED OR ILLEGIBLE TEXT OR DRAWING
| SKEWED/SLANTED IMAGES
| COLOR OR BLACK AND WHITE PHOTOGRAPHS
| GRAY SCALE DOCUMENTS
| LINES OR MARKS ON ORIGINAL DOCUMENT
| REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.